

# SOLIS

— THE TOUGHEST —  
**PERFORMER**  
« FOR YOUR FIELD »

## 26



RELIABLE MECHANICAL  
TRACTOR

POWER PACKED  
ENGINE

TWIN PROJECTOR  
HEADLAMPS

AGRI, IND. & TURF  
TYRE OPTION

REINFORCED SAFETY  
FEATURES



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

**STRATEGIC  
COLLABORATION  
WITH  
YANMAR**



**26**


**Solis**



FEATURES	<b>26</b>
<b>ENGINE</b>	
Engine Type	MHI Engine
HP Category	26
No. of Cylinders	3
Aspiration	Natural
Cubic Capacity (cc)	1318
Rated RPM	2700
Air Cleaner	Dry Type with Clogging Sensor
Cold Start	Standard
Max Torque (Nm)	76.3 Nm
Exhaust	Downdraft Exhaust
Muffler	Under-hood
<b>TRANSMISSION</b>	
Drive	4WD
Clutch	Single Clutch
Gearbox	6F+2R
Front Axle	4WD
Transmission	Sliding Mesh
<b>SPEED (FORWARD) Agri Tyre</b>	
Maximum Speed (Km/Hr)	18.08
Minimum Speed (Km/Hr)	1.67 @ 2700 rpm Speeds May Vary with Other Tyres
<b>BRAKES</b>	
Brakes	Oil Immersed Brakes
Type of Actuation	Mechanical
Parking Brake	Independent
<b>DIFFERENTIAL LOCK</b>	
Differential Lock	Mechanical, Foot Operated
<b>PTO</b>	
PTO (RPM)	540/1000
PTO (Actuation)	Mechanical
<b>STEERING</b>	
Steering	Power
<b>ELECTRICAL</b>	
Battery	12V, 65Ah
Alternator	12V, 42Amp
Seven Pin Trailer Socket	Output 12V
<b>HYDRAULICS</b>	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Hydraulic Lifting Capacity (kg)	600
Auxiliary Hydraulic Circuit	1DA
<b>SAFETY SWITCH</b>	
Clutch Safety Switch	Standard

FEATURES	<b>26</b>			
PTO Safety Switch	Standard			
Neutral Safety Switch	Standard			
<b>CAPACITY (Ltrs.) (+/-5%)</b>				
Fuel Tank (Ltr.)	26			
<b>TURNING RADIUS</b>				
With Brakes (m)	2.7			
<b>TYRE</b>				
Front	6.00 - 12			
Rear	8.30 - 20			
<b>DIMENSION &amp; WEIGHT (+/-5%) Agri Tyre</b>				
Weight (kg)	995			
Wheel Base (mm)	1560			
Total Length (mm)	2760			
Total Width (mm)	1075			
Height (mm) Up to ROPS	1955			
Min. Ground Clearance (mm)	240			
Front Track (mm)	885			
Rear Track (mm)	835			
<b>OTHERS</b>				
Fuel Indicator Gauge	Standard			
Front Tow Hook	Standard			
Front & Rear Weights with Std. Ballast (kg)	Front Weights 15x2			
Trailer Hitch	1. Swinging Bar (Optional) 2. Clevis Hitch (Standard) 3. Semi Automatic Hitch			
ROPS	Standard			
<b>OPTIONAL FEATURES</b>				
Canopy	Optional			
<b>TYRES</b>				
<b>TURF</b> Front Tyre: 23x8.50-12 Rear Tyre: 33x15.50-16.5	<b>INDUSTRIAL</b> Front Tyre: 23x8.50-12 Rear Tyre: 33x15.50-16.5	<b>AGRI</b> Front Tyre: 7x14 Rear Tyre: 8.3x24	<b>RADIAL</b> Front Tyre: 6.5/80-12 Rear Tyre: 280/70 R18	<b>GALAXY PRO</b> Front Tyre: 220/55 R12 Rear Tyre: 280/70 R16
Front End Loader	Optional			

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.



**INTERNATIONAL TRACTORS LIMITED**

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)  
 Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221  
 Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com